Automatic Distillation Testers – Performance Comparisons

Item	ADM-2E	PAC OptiDist	Another maker
Testing methods	JIS K2254, K2421, ASTM D86	Same as left	Same as left
Measuring range	Room Temp. to 300°C (DIST-7)	0 to 450°C	Room Temp. to 300°C (DIST-7)
	Room Temp. to 400°C (DIST-8)		Room Temp. to 400°C (DIST-8)
	Room Temp. to 300°C (BTX)		Room Temp. to 400°C (BTX)
Temperature	Platinum resistive element	Same as left	Same as left
sensor	thermometer		
First drop/Liquid	Photoelectric detector	Same as left	Same as left
level detection			
Distillation speed	4.5mL/min., 9.0mL/min.	2 to 10 mL/min.	2 to 9 mL/,on.
Heater	Nichrome-wire heater	Sheathed heater	Nichrome-wire heater
Cooling of heater	Time limit cooling by cooling fan	Cooling by cooling fan	Cooling by cooling fan
Cooling system for	By Pertier element (electronic	Cooling medium (Ethylene	By Pertier element (electronic
receiver room and	thermostat control) and water	Glycol) is used.	thermostat control) and metal
condensation tube	cooling circulation method		block method
Temperature of	15 to 40°C (possible up to	0 to 40°C	0 to 69.9°C
receiver chamber	60°C)		
Temperature of	0 to 60°C	0 to 65°C	0 to 69.9°C
condensation tube			
Display panel	LCD	TFT-LCD color	LCD
Input key	Push switches	Touch-keys on the screen	Switch panel
Printer	Graphic printer	Option	Thermal printer
USB port	Nil	3 ports	Nil
RS-232C port	2 ports	1 port	1 port
Eathernet	Nil	RJ45	Nil
Barometer	Built-in	Built-in	Option
Receiver chamber	Total receiver chamber,	Nil	Nil
mechanism	including cylinder, can be		
	purged by noncombustible N ₂		
	gas.		
Fire extinction	Injection of CO ₂ gas by ignition	Injection of CO ₂ gas by	Injection of CO ₂ gas by ignition
mechanism	fuses at 3 positions.	flame detectors at 2	fuse
		positions	
Earthquake	Built-in (to be tripped at the	Nil	Nil
detection	seismic intensity level 5)		
mechanism			
Dry point function	Built-in	Option	Option for automatic function
Volume-check	Distillation in a short time for	Nil	Nil
function	minimum 50mL is possible.		
Dimensions	46W x 53D x 59H cm	44W x 57D x 65H cm	40W x 52D x 71H cm
Weight	65kg	68kg	55kg